

NFPA 701 Method 2 Large Structure Material Compliance

** Custom Sizes Available **

ALL UNITS ARE SEALED AIR BEAM CONSTRUCTION

SPECIFICATIONS

	SMALL (4M)	MEDIUM (8M)	LARGE (9.5M)	X-LARGE (12M)	XX-LARGE (15M)	MEDICAL CLINIC
<u>Workspace Dimensions</u>						
<u>Length :</u>	10 ft	25 ft	30 ft	40 ft	50 ft	20 ft
<u>Width</u>	14 ft	13 ft	15 ft	15.5 ft	15.5 ft	30 ft
<u>Height</u>	7.9 ft	7.9 ft	9.5 ft	12.7 ft	12 ft	9 ft
<u>Material</u>	UPVC / Alloy-Coated Polyester / TPU / Polyplax Weave	UPVC / Alloy-Coated Polyester / TPU / Polyplax Weave	UPVC / Alloy-Coated Polyester / TPU / Polyplax Weave	UPVC / Alloy-Coated Polyester / TPU / Polyplax Weave	UPVC / Alloy-Coated Polyester / TPU / Polyplax Weave	UPVC / Alloy-Coated Polyester / TPU / Polyplax Weave
<u>Floor</u>	WOVEN UPVC	WOVEN UPVC	WOVEN UPVC	WOVEN UPVC	WOVEN UPVC	WOVEN UPVC
<u>Frame - Sealed Beam</u>	Polyplax Weave (Ripstop Material)	Polyplax Weave (Ripstop Material)	Polyplax Weave (Ripstop Material)	Polyplax Weave (Ripstop Material)	Polyplax Weave (Ripstop Material)	Polyplax Weave (Ripstop Material)
<u>Entrances / Exits</u>		2	2	2	2	2
<u>Emergency Egress Windows</u>	2 + 2 Exits	4 + 2 Exits	6 + 2 Exits	8 + 2 Exits	10 + 2 Exits	6 + 2 Exits
<u>Windows</u>		2	4	6	8	10
<u>Opening for Heater/ Hoses</u>		1	1	1	1	1
<u>Partiton Walls</u>	optional	optional	optional	optional	optional	N/A
<u>Clear Roof</u>	optional	optional	optional	optional	optional	N/A
<u>Tie Down Straps</u>		6	8	10	20	20
<u>Electric Frame Pump</u>						
Standard	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI
Automatic	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI	110V / 1000/2000 Watts/5.0 PSI
<u>Ventilation Blower</u> (Only Required for Negative Pressure Application)						
	3 Speed, WeatherProof ETL / CETL Safety Certified 1 HP / 3600CFM / 8.5 AMP Draw	3 Speed, WeatherProof ETL / CETL Safety Certified 1 HP / 3600CFM / 8.5 AMP Draw	3 Speed, WeatherProof ETL / CETL Safety Certified 1 HP / 3600CFM / 8.5 AMP Draw	3 Speed, WeatherProof ETL / CETL Safety Certified 1 HP / 3600CFM / 8.5 AMP Draw	3 Speed, WeatherProof ETL / CETL Safety Certified 1 HP / 3600CFM / 8.5 AMP Draw	3 Speed, WeatherProof ETL / CETL Safety Certified 1 HP / 3600CFM / 8.5 AMP Draw
<u>Logos</u>	optional	optional	optional	optional	optional	optional
<u>Packed Size / Inches</u>	38" H x 35" W x 35" D	41" H x 35" W x 35" D	43" H x 43" W x 36" D	53" H x 38" W x 48" D		
<u>Inner Floor Liner- Replaceable</u>	Removable Polyplax Weave	Removable Polyplax Weave	Removable Polyplax Weave	Removable Polyplax Weave	Removable Polyplax Weave	Removable Polyplax Weave
<u>High Pressure Air Lock Access</u>	3 ft	3 ft	3 ft	3 ft	3 ft	3 ft
<u>Filter Type</u>						
Input	Polyester/ Optional Hepa	Polyester/ Optional Hepa	Polyester/ Optional Hepa	Polyester/ Optional Hepa	Polyester/ Optional Hepa	N/A
Exhaust	3 Stage Polyester / Optional Hepa *Activated Charcoal Included	3 Stage Polyester / Optional Hepa *Activated Charcoal Included	3 Stage Polyester / Optional Hepa *Activated Charcoal Included	3 Stage Polyester / Optional Hepa *Activated Charcoal Included	3 Stage Polyester / Optional Hepa *Activated Charcoal Included	N/A
<u>Lighting</u>	Optional LED Strip Lights	Optional LED Strip Lights	Optional LED Strip Lights	Optional LED Strip Lights	Optional LED Strip Lights	Optional LED Strip Lights
<u>Ability to Heat & Cool</u>	Yes	Yes	Yes	Yes	Yes	Yes